

Pixel interpolation filters for video decompression processor

Publication number: EP0712249

Publication date: 1996-05-15

Inventor: HOOGENBOOM CHRIS (US); VUONG BAO (US)

Applicant: GEN INSTRUMENT CORP (US)

Classification:

- **international:** H04N7/32; H04N7/26; H04N7/36; H04N7/46; H04N7/50; H04N5/14; H04N7/32; H04N7/26; H04N7/36; H04N7/46; H04N7/50; H04N5/14; (IPC1-7): H04N7/24

- **europen:** H04N7/26L2; H04N7/26L4; H04N7/26M2S; H04N7/36C4; H04N7/46E; H04N7/50

Application number: EP19950116378 19951018

Priority number(s): US19940335651 19941108

Also published as:

US5638128 (A1)
JP8237662 (A)
EP0712249 (A3)
EP0712249 (B1)
DE69534408T (T2)

[more >>](#)


Cited documents:

EP0572263
EP0503956
EP0613304
XP000583293
XP000378969

[Report a data error here](#)

Abstract of EP0712249

A method and apparatus are disclosed for interpolating pixels (80) to obtain subpixels for use by a video decompression processor. A prediction area (90) is defined from which subpixels are necessary to decompress a portion of a video image. Instead of reading all of the pixels from the prediction area and then processing them together to perform the necessary interpolation, portions of the pixel data are read and simultaneously averaged using in-place computation in order to reduce hardware requirements. Rounding of subpixel results is achieved using the carry input of conventional adders (114, 116, 118, 120, 148) to add a binary "1" to the averaged pixels, which are subsequently truncated (150) to provide the interpolated subpixels.



Data supplied from the **esp@cenet** database - Worldwide